

## SPECIFICATION

### OXALIC ACID

**Code:** C3 130  
**CAS:** [144-62-7]  
**EINECS:** 205-634-3

	<b>Specification</b>	<b>Unit</b>
Appearance	white crystalline powder	/
Assay	min. 99,60	%
Sulphate (SO <sub>4</sub> )	≤ 15	ppm%
Ignition residue	≤ 10	ppm
Fe (Iron)	≤ 2	ppm
Zn (Zinc)	≤ 0,5	ppm
Mg (Magnesium)	≤ 0,5	ppm
Na (Sodium)	≤ 1	ppm
Pb (Lead)	≤ 0,5	ppm
K (Potassium)	≤ 2	ppm
Cu (Copper)	≤ 0,5	ppm
Ca (Calcium)	≤ 2	ppm
Sulfide (S)	≤ 5	ppm
Mn (Manganese)	≤ 0,5	ppm
Si (Silicon)	≤ 3	ppm
Cr (Chromium)	≤ 0,5	ppm
Ni (Nickel)	≤ 0,5	ppm
Ba (Barium)	≤ 0,5	ppm
Al (Aluminium)	≤ 0,5	ppm
As (Arsenic)	≤ 0,05	ppm
Cl (Chloride)	≤ 5	ppm
Heavy metals (as Pb)	≤ 1	ppm
Solubility in water	soluble	/